

FRONT VIEW



BOTTOM VIEW

ECHO pendant

120v **3-640-22**

277v **37-640-22**

OXYGEN LIGHTING ©

LAMPING

- o (4x) 10.1w LED arrays
- o 3000K, 350mA (ea.)
- o Initial Lumens: 4728 lm
- o Delivered Lumens: TBD
- o CRI>90
- o Color Consistency: 3 Step MacAdam Ellipse

DRIVER (Dimmable)

- o (4x) 0-10v & Reverse Phase Dimming Constant Current, 12w, 350mA

METAL FINISHES

- o **22** - Oiled Bronze
- o **24** - Satin Nickel

DIFFUSER

- o White Grass Shade with Matte White Acrylic

INPUT VOLTAGE

- o 120v OR 277v 50/60Hz

DIMENSIONS

- o Ø30.00" x 10.00"(h)

INSTALLATION

- o 4" Octagonal J-Box
- o ETL Dry/Damp Listed
- o ADA
- o Conforms to UL STD 1598
- o Certified CAN/CSA STD C22.2 No. 250.0

Sample Catalog Number

Series #	Finish	=	Catalog Number
3-640	**24**		3-640-**24**

oxygen

OXYGEN LIGHTING
201 RAILHEAD RD, FORT WORTH, TX 76106
TEL. (877) 607-0202 FAX (877) 607-0203
WWW.OXYGENLIGHTING.COM

PROJECT: _____

DATE: _____