


SIDE VIEW



BOTTOM VIEW

ECHO ceiling mount
 120v **3-694-24**
 277v **37-694-24**

OXYGEN LIGHTING ©

REVISED 11/21/16

LAMPING

- o (2x) 10.1w LED array
- o 3000K, 350mA (ea.)
- o Initial Lumens: 2364 lm
- o Delivered Lumens: TBD lm
- o CRI>90
- o Color Consistency: 3 Step MacAdam Ellipse

METAL FINISH

- o **24** - Satin Nickel

DIMENSIONS

- o Ø14.50" x 4.00"(h)

INSTALLATION

- o 4" Octagonal J-Box
- o ETL Dry/Damp Listed
- o Conforms to UL STD 1598
- o Certified CAN/CSA STD C22.2 No. 250.0

DRIVER (Dimmable)

- o (2x) 0-10v & Reverse Phase Dimming
- o Constant Current, 12w, 350mA

INPUT VOLTAGE

- o 120 OR 277v 50/60Hz

DIFFUSER

- o Matte White Acrylic
- o Natural Grass Shade

Sample Catalog Number



Series #	Finish	Catalog number
3-694	- 24	= 3-694-24

oxygen

OXYGEN LIGHTING
 201 RAILHEAD RD - FT WORTH, TX 76106
 TEL. (877) 607-0202 FAX (877) 607-0203
 WWW.OXYGENLIGHTING.COM

PROJECT: _____

DATE: _____

