

**ALTAIR Ceiling Mount**  
**3-334-xx**

oxygen

FIXTURE TYPE \_\_\_\_\_

LOCATION \_\_\_\_\_

PROJECT \_\_\_\_\_

DATE \_\_\_\_\_



**-22 Oiled Bronze**



**-24 Satin Nickel**



**-6 White**



**-15 Black**

**LIGHT SOURCE** 1 x 18.5W LED with Driver on board, 3000K, CRI 90

**LUMINAIRE POWER** 18.2W at 120V

**RATED LIFE** 30000 hr RL

**OPTIONAL COLOR TEMPERATURES** 3000K Only

**LUMEN OUTPUT** Delivered: 1064 lm (LM-79)

**INPUT VOLTAGE** 120V AC, 60Hz

**DRIVER OUTPUT** N/A

**DIMMING** TRIAC Dimming



**CONSTRUCTION** Cast Aluminum Housing with Steel Backplate

**DIFFUSER** - Etched White Glass

**FINISHES** White (-6), Black (-15),  
Oiled Bronze (-22), Satin Nickel (-24)

**MOUNTING** 4" Octagonal J-Box

**STANDARDS** ETL Damp listed, Conforms to UL STD 1598,  
Certified CAN/CSA STD C22.2 No 250.0.



**DIMENSIONS**

**W:** 9.125"

**L:** 9.125"

**H:** 1.00"

Order example for standard fixture:

**3-334-24** (x- Voltage - xxx-Sequence # - xx-Finish)

**3:** 120V Only

