

MIES Wall Sconce

120v : **3-520-xx**

277v : **37-520-xx**

oxygen

FIXTURE TYPE _____

LOCATION _____

PROJECT _____

DATE _____



-25 Satin Copper



-14 Polished Chrome




-24 Satin Nickel



-40 Aged Brass

LIGHT SOURCE	1 x 11.9W LED, 3000K, CRI 90
LUMINAIRE POWER	12.7W at 120V
RATED LIFE	60000 hr RL
OPTIONAL COLOR TEMPERATURES	2700K, 3500K, 4000K
LUMEN OUTPUT	Delivered: 730 lm (LM-79)
INPUT VOLTAGE	120V or 277V
DRIVER OUTPUT	350mA, 12W
DIMMING	0-10v & Phase (ELV) Dimming - 50/60Hz 100% to 10% Dimming
CONSTRUCTION	Plated Steel and Acrylic
DIFFUSER	- Matte White Acrylic
FINISHES	Polished Chrome (-14), Satin Nickel (-24), Satin Copper (-25), Aged Brass (-40)
MOUNTING	4" Octagonal J-Box with optional backplate, 2"x 3" J-Box
STANDARDS	ETL Dry/Damp listed, ADA compliant, Conforms to UL STD 1598, Certified CAN/CSA, STD C22.2 No 250.0.



DIMENSIONS

W:	3.00"
H:	21.75"
Ext:	3.88"
M.C:	19.00" From top of fixture
With optional backplate	
W:	4.75"
H:	22.00"
Ext:	4.00"
M.C:	19.00" From top of fixture

Order example for standard fixture:

3-520-24 (x- Voltage - xxx-Sequence # - xx-Finish)

3: 120v, 37: 277v

Order example for optional color temperatures: **3-520-2724**

27: 2700K, 35: 3500K, 40: 4000K

