

# HALO Wall Sconce

120v : **3-535-xx**

277v : **37-535-xx**

# oxygen

FIXTURE TYPE \_\_\_\_\_

LOCATION \_\_\_\_\_

PROJECT \_\_\_\_\_

DATE \_\_\_\_\_




-25 Satin Copper



-14 Polished Chrome



-24 Satin Nickel



-40 Aged Brass

**LIGHT SOURCE** 1 x 10.1W LED, 3000K, CRI 90

**LUMINAIRE POWER** 13.0W at 120V

**RATED LIFE** 60000 hr RL

**OPTIONAL COLOR TEMPERATURES** 2700K, 3500K, 4000K

**LUMEN OUTPUT** Delivered: 642 lm (LM-79)

**INPUT VOLTAGE** 120V or 277V

**DRIVER OUTPUT** 350 mA, 12W

**DIMMING** 0-10v & Phase (ELV) Dimming  
50/60Hz 100% to 10% Dimming

**CONSTRUCTION** Plated Steel and Acrylic

**DIFFUSER** - Matte White Acrylic

**FINISHES** Polished Chrome (-14), Satin Nickel (-24), Satin Copper (-25),  
Aged Brass (-40)

**MOUNTING** 4" Octagonal J-Box, 2"x3" J-Box\*  
\*J-Box must be mounted horizontally

**STANDARDS** ETL Dry/Damp listed, ADA compliant, Conforms to UL STD  
1598, Certified CAN/CSA, STD C22.2 No 250.0.

**NOTE** Backplate is required


Order example for standard fixture:

**3-535-24-BP24** (x- Voltage - xxx-Sequence # - xx-Finish -BPxx -Backplate Finish)

3: 120v, 37: 277v

Order example for optional color temperatures: **3-535-2724-BP24**

27: 2700K, 35: 3500K, 40: 4000K



## DIMENSIONS

**W:** 5.50"

**H:** 18.00"

**Ext:** 3.25"

**M.C:** 15.19" From top of fixture

