

FUSE Vanity
3-544-24

oxygen

FIXTURE TYPE _____ LOCATION _____
 PROJECT _____ DATE _____



-24 Satin Nickel

LIGHT SOURCE 2 x 10.1W LED, 3000K, CRI 90
LUMINAIRE POWER 24.1W at 120V
RATED LIFE 60000 hr RL
OPTIONAL COLOR TEMPERATURES 2700K, 3500K, 4000K
LUMEN OUTPUT Delivered: 1810 lm (LM-79)
INPUT VOLTAGE 120V to 277V AC, 50/60Hz
DRIVER OUTPUT 700mA, 29.4W max power
DIMMING TRIAC and ELV dimming at 120V AC; 0-10V dimming, 100% to 1% current output
CONSTRUCTION Plated Steel and Acrylic
DIFFUSER - Matte White Acrylic
FINISHES Satin Nickel (-24)
MOUNTING 4" Octagonal J-Box*
 *Deep J-Box (Required to house driver)
STANDARDS UL Dry/Damp listed, ADA Compliant, Conforms to UL STD 1598, Certified CAN/CSA STD C22.2 No 250.0.



DIMENSIONS

W: 26.00"
H: 5.00"
Ext: 4.00"
M.C: 2.50" From top of fixture

Order example for standard fixture:
3-544-24 (x- Voltage - xxx-Sequence # - xx-Finish)
 3: 120V to 277V
 Order example for optional color temperatures: **3-544-2724**
 27: 2700K, 35: 3500K, 40: 4000K

