

BALANCE Vanity
3-549-xx-BPxx

oxygen

FIXTURE TYPE _____ LOCATION _____
 PROJECT _____ DATE _____




-20 Polished Nickel



-24 Satin Nickel

LIGHT SOURCE	2 x 11.6W LED, 3000K, CRI 90
LUMINAIRE POWER	28.6W at 120V
RATED LIFE	60000 hr RL
OPTIONAL COLOR TEMPERATURES	2700K, 3500K, 4000K
LUMEN OUTPUT	Delivered: 2022 lm (LM-79)
INPUT VOLTAGE	120V to 277V AC, 50/60Hz
DRIVER OUTPUT	700mA, 29.4W max
DIMMING	TRIAC and ELV dimming at 120V AC; 0-10V dimming, 100% to 10% current output
CONSTRUCTION	Plated Steel and Acrylic
DIFFUSER	- Matte White Acrylic
FINISHES	Polished Nickel (-20), Satin Nickel (-24)
MOUNTING	4" Octagonal J-Box*, 4"x4" J-Box* with a single device mud ring *Deep J-Box (Required to house driver)
STANDARDS	UL Dry/Damp listed, ADA Compliant, Conforms to UL STD 1598, Certified CAN/CSA, STD C22.2 No 250.0.



DIMENSIONS

W:	52.75"
H:	4.50"
Ext:	4.00"
M.C:	2.25" From top of fixture

Order example for standard fixture:

3-549-24-BP24

(x- Voltage - xxx-Sequence # - xx-Finish - BPxx- Backplate Finish)

3: 120V to 277V

Order example for optional color temperatures: **3-549-2724-BP24**

27: 2700K, 35: 3500K, 40: 4000K

