

AURORA Ceiling Mount / Wall Sconce

3-662-xx

oxygen

FIXTURE TYPE _____

LOCATION _____

PROJECT _____

DATE _____



-24 Satin Nickel





-15 Black



-20 Polished Nickel

LIGHT SOURCE	1 x 21.5W LED, 3000K, CRI 90
LUMINAIRE POWER	25.1W at 120V
RATED LIFE	60000 hr RL
OPTIONAL COLOR TEMPERATURES	2700K, 3500K, 4000K
LUMEN OUTPUT	Delivered: 1084 lm (LM-79)
INPUT VOLTAGE	120V to 277V AC, 50/60Hz
DRIVER OUTPUT	700mA, 29.4W max
DIMMING	TRIAC and ELV dimming at 120V AC; 0-10V dimming, 100% to 10% current output
CONSTRUCTION	Plated Steel and Acrylic
DIFFUSER	Matte White Acrylic
FINISHES	Black (-15), Polished Nickel (-20), Satin Nickel (-24)
MOUNTING	4" Octagonal J-Box* 4"x4" Square J-Box* with single device mud ring * Deep J-Box (Required to house driver)
STANDARDS	UL Dry/Damp listed, ADA Compliant, Conforms to UL STD 1598, Certified CAN/CSA, STD C22.2 No 250.0.



Dia.

DIMENSIONS
Dia: 13.50"
Ext: 4.00"
M.C: 6.75" From Top of Fixture

Order example for standard fixture:

3-662-xx (x-Voltage - xxx-Sequence # - xx-Finish)

Order example for optional color temperatures: **3-662-2724**

27: 2700K, **35:** 3500K, **40:** 4000K

