

MODULO Ceiling Mount

120v: **3-682-xx**

277v: **37-682-xx**

oxygen

FIXTURE TYPE _____

LOCATION _____

PROJECT _____

DATE _____





-24 Satin Nickel



-40 Aged Brass

LIGHT SOURCE	1 x 10.1W LED, 3000K, CRI 90
LUMINAIRE POWER	13.2W at 120V
RATED LIFE	60000 hr RL
OPTIONAL COLOR TEMPERATURES	2700K, 3500K, 4000K
LUMEN OUTPUT	Delivered: 905 lm (LM-79)
INPUT VOLTAGE	120V or 277V
DRIVER OUTPUT	350mA, 12W
DIMMING	0-10v & Phase (ELV) Dimming - 50/60Hz 100% to 10% Dimming
CONSTRUCTION	Plated Steel and Acrylic
DIFFUSER	- Matte White Acrylic
FINISHES	Satin Nickel (-24), Aged Brass (-40)
MOUNTING	4" Octagonal J-Box
STANDARDS	ETL Dry/Damp listed, Conforms to UL STD 1598, Certified CAN/CSA, STD C22.2 No 250.0.



DIMENSIONS
W: 12.00"
L: 12.00"
H: 4.90"

Order example for standard fixture:

3-682-24 (x- Voltage - xxx-Sequence # - xx-Finish)

3: 120v, **37:** 277v, **32:** Universal Voltage

Order example for optional color temperatures: **3-682-2724**

27: 2700K, **35:** 3500K, **40:** 4000K

