

# ECHO Ceiling Mount

120v: **3-694-xx-EM**

277v: **37-694-xx-EM**

# oxygen

FIXTURE TYPE \_\_\_\_\_

LOCATION \_\_\_\_\_



PROJECT \_\_\_\_\_

DATE \_\_\_\_\_



-24 Satin Nickel

<b>LIGHT SOURCE</b>	2 x 10.1W LED, 3000K, CRI 90
<b>LUMINAIRE POWER</b>	25.7W at 120V
<b>RATED LIFE</b>	60000 hr RL
<b>OPTIONAL COLOR TEMPERATURES</b>	2700K, 3500K, 4000K
<b>LUMEN OUTPUT</b>	Delivered: 1277 lm (LM-79)
<b>INPUT VOLTAGE</b>	120V or 277V
<b>DRIVER OUTPUT</b>	2 x 350mA, 12W
<b>DIMMING</b>	0-10v & Phase (ELV) Dimming - 50/60Hz 100%to 10% Dimming
<b>CONSTRUCTION</b>	Plated Steel and Acrylic / Fabric
<b>DIFFUSER</b>	- White Grass and Matte White Acrylic
<b>FINISHES</b>	Satin Nickel (-24)
<b>MOUNTING</b>	4" Octagonal J-Box
<b>STANDARDS</b>	ETL Dry/Damp listed, Conforms to UL STD 1598, Certified CAN/CSA, STD C22.2 No 250.0.



**DIMENSIONS**  
**Dia:** 14.50"  
**H:** 4.00"

<b>EM Driver</b>	Fullham HotspotLED Series
<b>EM Battery Life</b>	90 Minutes Minimum

Order example for standard fixture:

**3-694-24-EM** (x- Voltage - xxx-Sequence # - xx-Finish)

3: 120v, 37: 277v

Order example for optional color temperatures: **3-694-2724-EM**

27: 2700K, 35: 3500K, 40: 4000K

