

FIXTURE TYPE _____

LOCATION _____

PROJECT _____

DATE _____





-22 Oiled Bronze



-24 Satin Nickel

LIGHT SOURCE	2 x 10.1W LED, 3000K, CRI 90
LUMINAIRE POWER	25.9W at 120V
RATED LIFE	60000 hr RL
LUMEN OUTPUT	Delivered: 1172 lm (LM-79)
INPUT VOLTAGE	120V to 277V AC, 50/60Hz
DRIVER OUTPUT	700mA, 29.4W
DIMMING	TRIAC and ELV dimming at 120V AC; 0-10V dimming, 100% to 10% current output
CONSTRUCTION	Cast Aluminum and Acrylic
DIFFUSER	-2 Matte White Acrylic
FINISHES	Oiled Bronze (-22), Satin Nickel (-24)
MOUNTING	4" Octagonal J-Box (Installer must provide a bead of caulk between fixture housing and mounting surface)
STANDARDS	ETL Wet, Conforms to UL STD 1598, Certified CAN/CSA, STD C22.2 No 250.0.



DIMENSIONS

W:	9.00"
H:	21.75"
Ext:	5.00"
M.C:	10.81" From top of fixture

EM Battery Life	Fullham HotspotLED Series
EM Battery Life	90 Minutes Minimum

Order example for standard fixture:
3-711-224-EM (x- Voltage - xxx-Sequence # - x-Diffuser - xx-Finish)
3: 120V, **37:** 277V

