

ERIS Outdoor

120v : **3-720-xx**

277v : **37-720-xx**

oxygen

FIXTURE TYPE _____

LOCATION _____

PROJECT _____

DATE _____






-22 Oiled Bronze



-16 Gray

LIGHT SOURCE	1 x 8.4W LED, 3000K, CRI 90
LUMINAIRE POWER	10.4W at 120V
RATED LIFE	60000 hr RL
OPTIONAL COLOR TEMPERATURES	2700K, 3500K, 4000K
LUMEN OUTPUT	Delivered: 529 lm (LM-79)
INPUT VOLTAGE	120V or 277V
DRIVER OUTPUT	350 mA, 12W
DIMMING	0-10v & Phase (ELV) Dimming - 50/60Hz 100% to 10% Dimming
CONSTRUCTION	Cast Aluminium and Glass
DIFFUSER	- Frosted Glass
FINISHES	Gray (-16), Oiled Bronze (-22)
MOUNTING	4" Octagonal J-Box*, 4" Square J-Box* *Deep J-Box (Installer must provide a bead of caulk between fixture housing and mounting surface)
STANDARDS	ETL Wet, Conforms to UL STD 1598, Certified CAN/CSA, STD C22.2 No 250.0



DIMENSIONS

- W:** 6.00"
- H:** 4.75"
- Ext:** 4.35"
- M.C:** 2.37" From top of fixture

Order example for standard fixture:

3-720-22 (x- Voltage - xxx-Sequence # - xx-Finish)

3: 120v, **37:** 277v, **32:** Universal Voltage

Order example for optional color temperatures: **3-720-2722**

27: 2700K, **35:** 3500K, **40:** 4000K

