

# CERES Outdoor

120v : **3-727-xx**  
277v : **37-727-xx**

# oxygen

FIXTURE TYPE \_\_\_\_\_ LOCATION \_\_\_\_\_

PROJECT \_\_\_\_\_ DATE \_\_\_\_\_






-16 Gray



-22 Oiled Bronze

<b>LIGHT SOURCE</b>	2 x 8.2W LED, 3000K, CRI 90
<b>LUMINAIRE POWER</b>	20.7W at 120V
<b>RATED LIFE</b>	60000 hr RL
<b>OPTIONAL COLOR TEMPERATURES</b>	2700K, 3500K, 4000K
<b>LUMEN OUTPUT</b>	Delivered: 897 lm (LM-79)
<b>INPUT VOLTAGE</b>	120V or 277V
<b>DRIVER OUTPUT</b>	2 x 350 mA, 12W
<b>DIMMING</b>	0-10v & Phase (ELV) Dimming - 50/60Hz 100% to 10% Dimming
<b>CONSTRUCTION</b>	Cast Aluminium and Glass
<b>DIFFUSER</b>	- Frosted Glass
<b>FINISHES</b>	Gray (-16), Oiled Bronze (-22)
<b>MOUNTING</b>	4" Octagonal J-Box*, 4" Squared J-Box* *Deep J-Box (Installer must provide a bead of caulk between fixture housing and mounting surface)
<b>STANDARDS</b>	ETL Wet, Conforms to UL STD 1598, Certified CAN/CSA, STD C22.2 No 250.0.



## DIMENSIONS

**W:** 4.75"

**H:** 4.75"

**Ext:** 5.00"

**M.C:** 2.37" From top of fixture

Order example for standard fixture:

**3-727-22** (x- Voltage - xxx-Sequence # - xx-Finish)

**3:** 120v, **37:** 277v, **32:** Universal Voltage

Order example for optional color temperatures: **3-727-2722**

**27:** 2700K, **35:** 3500K, **40:** 4000K

