

# CALYPSO Outdoor

120v : **3-730-xx**

277v : **37-730-xx**

# oxygen

FIXTURE TYPE \_\_\_\_\_

LOCATION \_\_\_\_\_

PROJECT \_\_\_\_\_

DATE \_\_\_\_\_





-22 Oiled Bronze



-16 Gray

- LIGHT SOURCE** 1 x 10.1W LED, 3000K, CRI 90
- LUMINAIRE POWER** 13.0W at 120V
- RATED LIFE** 60000 hr RL
- OPTIONAL COLOR TEMPERATURES** 2700K, 3500K, 4000K
- LUMEN OUTPUT** Delivered: 531 lm (LM-79)
- INPUT VOLTAGE** 120V or 277V
- DRIVER OUTPUT** 350 mA, 12W
- DIMMING** 0-10v & Phase (ELV) Dimming - 50/60Hz 100% to 10% Dimming
- CONSTRUCTION** Cast Aluminium and Polycarbonate
- DIFFUSER** - Polished White Polycarbonate
- FINISHES** Gray (-16), Oiled Bronze (-22)
- MOUNTING** 4" Octagonal J-Box  
(Installer must provide a bead of caulk between fixture housing and mounting surface)
- STANDARDS** ETL Wet, ADA compliant, Conforms to UL STD 1598, Certified CAN/CSA, STD C22.2 No 250.0.



## DIMENSIONS

**W:** 4.25"

**H:** 16.50"

**Ext:** 2.25"

**M.C:** 8.00" From top of fixture

Order example for standard fixture:

**3-730-22** (x- Voltage - xxx-Sequence # - xx-Finish)

**3:** 120v, **37:** 277v, **32:** Universal Voltage

Order example for optional color temperatures: **3-730-2722**

**27:** 2700K, **35:** 3500K, **40:** 4000K

