

ZURI Ceiling Mount

32-630-xx

oxygen

FIXTURE TYPE _____ LOCATION _____


PROJECT _____ DATE _____



-24 Satin Nickel



-15 Black



-40 Aged Brass

LIGHT SOURCE 1 x 8.2W LED, 3000K, CRI 90

LUMINAIRE POWER 10.1W at 120V

RATED LIFE 60000 hr RL

OPTIONAL COLOR TEMPERATURES 2700K, 3500K, 4000K

LUMEN OUTPUT Delivered: 542 lm (LM-79)

INPUT VOLTAGE 120V to 277V AC, 50/60Hz

DRIVER OUTPUT 350mA, 14.7W max

DIMMING TRIAC and ELV dimming at 120V AC;
0-10V dimming, 100% to 10% current output


CONSTRUCTION Plated Steel and Glass

DIFFUSER - White Opal Glass

FINISHES Black (-15), Satin Nickel (-24), Aged Brass (-40)

MOUNTING 4"x4" Square J-Box*
*Deep J-Box (Required to house driver)

STANDARDS UL Dry/Damp listed, ADA Compliant, Conforms to UL STD 1598,
Certified CAN/CSA, STD C22.2 No 250.0.



DIMENSIONS
Dia: 7.25"
H: 2.80"

Order example for standard fixture:

32-630-xx (x-Voltage - xxx-Sequence # - xx-Finish)

Order example for optional color temperatures: **32-630-2724**

27: 2700K, **35:** 3500K, **40:** 4000K

