

# ZURI Ceiling Mount

## 32-631-xx


oxygen

FIXTURE TYPE \_\_\_\_\_ LOCATION \_\_\_\_\_


PROJECT \_\_\_\_\_ DATE \_\_\_\_\_



-24 Satin Nickel





-15 Black



-40 Aged Brass

<b>LIGHT SOURCE</b>	1 x 21.1W LED, 3000K, CRI 90
<b>LUMINAIRE POWER</b>	23.5W at 120V
<b>RATED LIFE</b>	60000 hr RL
<b>OPTIONAL COLOR TEMPERATURES</b>	2700K, 3500K, 4000K
<b>LUMEN OUTPUT</b>	Delivered: 1328 lm (LM-79)
<b>INPUT VOLTAGE</b>	120V to 277V AC, 50/60Hz
<b>DRIVER OUTPUT</b>	700mA, 30W max
<b>DIMMING</b>	0-10V dimming, 100% to 10% current output
<b>CONSTRUCTION</b>	Plated Steel and Glass
<b>DIFFUSER</b>	- White Opal Glass
<b>FINISHES</b>	Black (-15), Satin Nickel (-24), Aged Brass (-40)
<b>MOUNTING</b>	4" Octagonal J-Box
<b>STANDARDS</b>	UL Dry/Damp listed, ADA Compliant, Conforms to UL STD 1598, Certified CAN/CSA, STD C22.2 No 250.0.



**DIMENSIONS**  
**Dia: 11.25"**  
**H: 3.00"**

Order Example for standard fixture:

**32-631-xx** (x-Voltage - xxx-Sequence # - xx-Finish)

Order example for optional color temperatures: **32-631-2724**

**27:** 2700K, **35:** 3500K, **40:** 4000K

