

# DIONE Ceiling Mount

Universal Voltage: **32-665-xx**

# oxygen

FIXTURE TYPE \_\_\_\_\_

LOCATION \_\_\_\_\_


PROJECT \_\_\_\_\_

DATE \_\_\_\_\_



-24 Satin Nickel

<b>LIGHT SOURCE</b>	1 x 21.1W LED, 3000K, CRI 90
<b>LUMINAIRE POWER</b>	23.5W at 120V
<b>RATED LIFE</b>	60000 hr RL
<b>OPTIONAL COLOR TEMPERATURES</b>	2700K, 3500K, 4000K
<b>LUMEN OUTPUT</b>	Delivered: 807 lm (LM-79)
<b>INPUT VOLTAGE</b>	Universal Voltage 120V-277V
<b>DRIVER OUTPUT</b>	700mA, 30W
<b>DIMMING</b>	0-10v - 50/60Hz 100% to 10% Dimming
<b>CONSTRUCTION</b>	Plated Steel and Glass
<b>DIFFUSER</b>	- Frosted Glass
<b>FINISHES</b>	Satin Nickel (-24)
<b>MOUNTING</b>	4" Octagonal J-Box
<b>STANDARDS</b>	ETL Dry/Damp listed, Conforms to UL STD 1598, Certified CAN/CSA, STD C22.2 No 250.0.



**DIMENSIONS**  
**Dia:** 21.06"  
**H:** 2.45"

Order example for standard fixture:

**32-665-24** (x- Voltage - xxx-Sequence # - xx-Finish)

3: 120v, 37: 277v, 32: Universal Voltage

Order example for optional color temperatures: **32-665-2724**

27: 2700K, 35: 3500K, 40: 4000K

