



28" APOLLO vanity
 120V **3-524-14**
 277V **37-524-14**

OXYGEN LIGHTING ©

- | | | | | |
|--|---|--|---|---|
| <p>LAMPING</p> <ul style="list-style-type: none"> <input type="checkbox"/> (2x) 10.1w LED array <input type="checkbox"/> 3000K, 350mA (ea.) <input type="checkbox"/> Initial Lumens: 2920 lm <input type="checkbox"/> Delivered Lumens: TBD <input type="checkbox"/> CRI>80 <input type="checkbox"/> Color Consistency: 3 Step Macadam Ellipse | <p>DRIVER (Dimmable)</p> <ul style="list-style-type: none"> <input type="checkbox"/> (2x) 0-10v & Reverse Phase Dimming, Constant Current, 12w, 350mA | <p>METAL FINISHES</p> <ul style="list-style-type: none"> <input type="checkbox"/> 14 - Polished Chrome <input type="checkbox"/> 22 - Oiled Bronze <input type="checkbox"/> 24 - Satin Nickel <input type="checkbox"/> 40 - Aged Brass | <p>DIMENSIONS</p> <ul style="list-style-type: none"> <input type="checkbox"/> 27.75" (w) x 2.75" (h) x 2.50" (ext.) | <p>INSTALLATION</p> <ul style="list-style-type: none"> <input type="checkbox"/> 2" x 3" J-Box <input type="checkbox"/> ETL Dry/Damp Listed <input type="checkbox"/> ADA <input type="checkbox"/> Conforms to UL STD 1598 <input type="checkbox"/> Certified CAN/CSA STD C22.2 No. 250.0 |
| <p>INPUT VOLTAGE</p> <ul style="list-style-type: none"> <input type="checkbox"/> 120V OR 277v 50/60HZ | | <p>DIFFUSER</p> <ul style="list-style-type: none"> <input type="checkbox"/> Matte White Acrylic | | |

Sample Catalog Number



Series # 3-524 - Finish 24 = Catalog number 3-524-24

PROJECT: _____

Oxygen

OXYGEN LIGHTING
 201 RAILHEAD RD, FORT WORTH, TX 76106
 TEL. (877) 607-0202 FAX (877) 607-0203
 WWW.OXYGENLIGHTING.COM

DATE: _____

