



**OXYGEN LIGHTING ©**

**LAMPING**

- (2x) 10.1w LED array
- 3000K, 350mA (ea.)
- Initial Lumens: 2920 lm
- Delivered Lumens: TBD
- CRI>80
- Color Consistency: 3 Step Macadam Ellipse

**DRIVER (Dimmable)**

- (2x) 0-10v & Reverse Phase Dimming, Constant Current, 12w, 350mA

**INPUT VOLTAGE**

- 120V OR 277v 50/60HZ

**METAL FINISHES**

- 14** - Polished Chrome
- 22** - Oiled Bronze
- 24** - Satin Nickel
- 40** - Aged Brass

**DIFFUSER**

- Matte White Acrylic

**DIMENSIONS**

27.75" (w) x 2.75" (h) x 2.50" (ext.)

**INSTALLATION**

- 2" x 3" J-Box
- ETL Dry/Damp Listed
- ADA
- Conforms to UL STD 1598
- Certified CAN/CSA STD C22.2 No. 250.0

**28" APOLLO vanity**  
**120V 3-524-22**  
**277V 37-524-22**

Sample Catalog Number



Series # 3-524 - Finish 24 = Catalog number 3-524-24

PROJECT: \_\_\_\_\_

**Oxygen**

OXYGEN LIGHTING

201 RAILHEAD RD, FORT WORTH, TX 76106

TEL. (877) 607-0202 FAX (877) 607-0203

WWW.OXYGENLIGHTING.COM

DATE: \_\_\_\_\_

