



OXYGEN LIGHTING ©

LAMPING

- (2x) 10.1w LED array
- 3000K, 350ma (ea.)
- Initial Lumens: 2920 lm
- Delivered Lumens: TBD
- CRI>80
- Color Consistency: 3 Step Macadam Ellipse

DRIVER (Dimmable)

- (2x) 0-10v & Reverse Phase Dimming, Constant Current, 12w, 350ma

INPUT VOLTAGE

- 120V OR 277v 50/60HZ

METAL FINISHES

- 14** - Polished Chrome
- 22** - Oiled Bronze
- 24** - Satin Nickel
- 40** - Aged Brass

DIFFUSER

- Matte White Acrylic

DIMENSIONS

- 27.75" (w) x 2.75" (h) x 2.50" (ext.)

INSTALLATION

- 2" x 3" J-Box
- ETL Dry/Damp Listed
- ADA
- Conforms to UL STD 1598
- Certified CAN/CSA STD C22.2 No. 250.0

28" APOLLO vanity
120V 3-524-24
277V 37-524-24

Sample Catalog Number



Series # 3-524 - Finish 24 = Catalog number 3-524-24

PROJECT: _____

Oxygen

OXYGEN LIGHTING
 201 RAILHEAD RD, FORT WORTH, TX 76106
 TEL. (877) 607-0202 FAX (877) 607-0203
 WWW.OXYGENLIGHTING.COM

DATE: _____

