



OXYGEN LIGHTING ©

LAMPING

- o (2x) 10.1w LED array
- o 3000K, 350mA (ea.)
- o Initial Lumens: 2920 lm
- o Delivered Lumens: TBD
- o CRI > 80
- o Color Consistency: 3 Step Macadam Ellipse

DRIVER (Dimmable)

- o (2x) 0-10v & Reverse Phase Dimming, Constant Current, 12w, 350mA

METAL FINISHES

- o 14 - Polished Chrome
- o 22 - Oiled Bronze
- o 24 - Satin Nickel
- o 40 - Aged Brass

DIMENSIONS

- o 32.00" (w) x 2.75" (h) x 2.50" (ext.)

INSTALLATION

- o 2" x 3" "J" - Box
- o ETL Dry/Damp Listed
- o ADA
- o Conforms to UL STD 1598 Certified CAN/CSA STD C22.2 No. 250.0

INPUT VOLTAGE

- o 120v OR 277v 50/60Hz

DIFFUSER

- o Matte White Acrylic

Sample Catalog Number



32" APOLLO vanity
120V 3-525-14
277V 37-525-14

Oxygen

OXYGEN LIGHTING
 201 RAILHEAD RD, FORT WORTH, TX 76106
 TEL. (877) 607-0202 FAX (877) 607-0203
 WWW.OXYGENLIGHTING.COM

Series # 3-525 - Finish 24 = Catalog number 3-525-24

PROJECT: _____

DATE: _____

