



MIZAR sconce
 120v **3-550-22**
 277v **37-550-22**

OXYGEN LIGHTING ©

LAMPING

- o (1x) 10.2w LED Array
- o 3000k, 350mA
- o Initial Lumens: 1460 lm
- o Delivered Lumens: 649 lm
- o CRI > 80
- o Color Consistency: 3 step MacAdam Ellipse

METAL FINISHES

- o **22** - Oiled Bronze
- o **24** - Satin Nickel
- o **40** - Aged Brass

DIMENSIONS

- o 12.00" (w) X 4.88" (h) X 2.69" (ext.)

INSTALLATION

- o 2" x 3" J - Box
- o 4" x 4" J - Box
- o ETL Dry/Damp Listed
- o ADA
- o Conforms to US STD 1598
- o Certified CAN/CSA STD C22.2 No. 250.0

DIFFUSER

- o Matte White Acrylic

DRIVER (Dimmable)

- o (1x) 0-10v & Reverse Phase Dimming Constant Current, 12W, 350mA

INPUT VOLTAGE

- o 120v OR 277v 50/60Hz

Sample Catalog Number

Series #	Finish	=	Catalog Number
3-550	24	=	3-550-24



oxygen

OXYGEN LIGHTING
 201 RAILHEAD RD, FORT WORTH, TX 76106
 TEL. (877) 607-0202 FAX (877) 607-0203
 WWW.OXYGENLIGHTING.COM

PROJECT: _____
 DATE: _____

