



OXYGEN LIGHTING ©

Zenith vanity
 120V **3-559-24**
 277V **37-559-24**

LAMPING

- o (2x) 11.6w LED array
- o 3000K, 350mA (ea.)
- o Initial Lumens: 3758 lm
- o Delivered Lumens: 2356 lm
- o CRI>80
- o Color Consistency: 3 Step MacAdam Ellipse

DRIVER (Dimming)

- o (2x) 0-10v & Reverse Phase Dimming, Constant Current, 12w, 350mA

INPUT VOLTAGE

- o 120V OR 277V 50/60Hz

METAL FINISHES

- o 14 - Polished Chrome
- o 24 - Satin Nickel

DIFFUSER

- o Matte White Acrylic

DIMENSIONS

- o 48.82" (w) x 2.50" (h) x 3.32" (ext.)

INSTALLATION

- o 2" x 3" J-Box
- o ETL Dry/Damp Listed
- o ADA
- o Conforms to UL STD 1598 Certified CAN/CSA STD C22.2 No. 250.0

Sample Catalog Number



Series # **3-559** - Finish **14** = Catalog number **3-559-14**

oxygen

OXYGEN LIGHTING
 201 RAILHEAD RD, FORT WORTH, TX 76106
 TEL. (877) 607-0202 FAX (877) 607-0203
 WWW.OXYGENLIGHTING.COM

PROJECT: _____
 DATE: _____

