



**TOP VIEW**



**SIDE VIEW**



**FRONT VIEW**

**SIREN** sconce  
 120v **3-563-414**  
 277v **37-563-414**

OXYGEN LIGHTING ©

**LAMPING**

- o (1x) 10.1w Array
- o 3000K, 350mA
- o Initial Lumens: 1460 lm
- o Delivered Lumens: TBD
- o CRI > 80
- o Color Consistency: 3 step MacAdam Ellipse

**METAL FINISH**

- o 14 - Polished Chrome
- o 24 - Satin Nickel

**DIMENSIONS**

- o 7.91" (w) x 12.50" (h) x 4.00" (ext.)

**INSTALLATION**

- o 4" Octagonal J-Box
- o ETL Dry/Damp Listed
- o Wall mount
- o ADA
- o Conforms to UL STD 1598
- o Certified CAN/CSA STD C22.2 No. 250.0

**DRIVER (Dimmable)**

- o (1x) 0-10v & Reverse Phase Dimming Constant Current, 12w, 350mA

**DIFFUSERS**

- o 1 - White Opal Glass
- o 2 - Matte White Acrylic
- o 4 - Faux Onyx Acrylic
- o 6 - Silver Cloth Acrylic

**INPUT VOLTAGE**

- o 120v OR 277v 50/60Hz

**Sample Catalog Number**



Series #	Diffuser	Finish	Catalog number
3-563	- 2	14	= 3-563-214

**oxygen**

**OXYGEN LIGHTING**  
 201 RAILHEAD RD, FORT WORTH, TX 76106  
 TEL. (877) 607-0202 FAX (877) 607-0203  
 WWW.OXYGENLIGHTING.COM

PROJECT: \_\_\_\_\_  
 DATE: \_\_\_\_\_

