


FRONT VIEW



BOTTOM VIEW

ORACLE ceiling mount
 120v **3-618-40**
 277v **37-618-40**

OXYGEN LIGHTING ©

LAMPING

- o (1x) 8.2w LED Array
- o 3000K, 350mA
- o Initial Lumens: 1173 lm
- o Delivered Lumens: TBD
- o CRI > 80
- o Color Consistency: 3 Step MacAdam Ellipse

DRIVER (Dimmable)

- o (1x) 0-10v & Reverse Phase Dimming Constant Current, 12w, 350mA

METAL FINISHES

- o 14 - Polished Chrome
- o 22 - Oiled Bronze
- o 24 - Satin Nickel
- o 40 - Aged Brass

DIFFUSER

- o Matte White Acrylic

INPUT VOLTAGE

- o 120v OR 277v 50/60Hz

DIMENSIONS

- o Ø10.38" x 3.44"(h)

INSTALLATION

- o 4" Octagonal J-Box
- o Approved for ceiling or wall mounting
- o Conforms to UL STD 1598
- o Certified CAN/CSA STD C22.2 No. 250.0

Sample Catalog Number



Series #	Finish	Catalog number
3-618	- 24	= 3-618-24

oxygen

OXYGEN LIGHTING
 201 RAILHEAD RD, FORT WORTH, TX 76106
 TEL. (877) 607-0202 FAX (877) 607-0203
 WWW.OXYGENLIGHTING.COM

PROJECT: _____
 DATE: _____