



ECHO pendant
 120v **3-638-22**
 277v **37-638-22**

OXYGEN LIGHTING ©

LAMPING

- o (3x) 10.1w LED array
- o 3000K, 350mA (ea.)
- o Initial Lumens: 4380 lm
- o Delivered Lumens: TBD
- o CRI>80
- o Color Consistency: 3 Step MacAdam Ellipse

DRIVER (Dimmable)

- o (3x) 0-10v & Reverse Phase Dimming Constant Current, 12w, 350mA

METAL FINISHES

- o **22** - Oiled Bronze
- o **24** - Satin Nickel

DIFFUSER

- o White Grass Shade with Matte White Acrylic

INPUT VOLTAGE

- o 120v OR 277v 50/60Hz

DIMENSIONS

- o Ø18.00" x10.59"(h)

INSTALLATION

- o 4" Octagonal J-Box
- o ETL Dry/Damp Listed
- o ADA
- o Conforms to UL STD 1598
- o Certified to CAN/CSA STD C22.2 No. 250.0

Sample Catalog Number

Series #	Finish	=	Catalog Number
3-638	24	=	3-638-24



oxygen

OXYGEN LIGHTING
 201 RAILHEAD RD, FORT WORTH, TX 76106
 TEL. (877) 607-0202 FAX (877) 607-0203
 WWW.OXYGENLIGHTING.COM

PROJECT: _____

DATE: _____