



**ERIS** outdoor  
 120v **3-721-22**  
 277v **37-721-22**

OXYGEN LIGHTING ©

**LAMPING**

- o (2x) 8.2w LED Arrays
- o 3000K, 350mA (ea.)
- o Initial Lumens: 2346 lm
- o Delivered Lumens: 812 lm
- o CRI>80
- o Color Consistency: 3 Step MacAdam Ellipse

**DRIVER (Dimmable)**

- o (2x) 0-10v & Reverse Phase Dimming Constant Current, 12w, 350mA

**METAL FINISHES**

- (All finishes polyester powder coat)
- o **16** - Gray
  - o **22** - Oiled Bronze

**DIFFUSER**

- o Clear Frosted Glass

**INPUT VOLTAGE**

- o 120v OR 277v 50/60Hz

**DIMENSIONS**

- o 6.00" (w) x 4.75" (h) X 4.35" (ext.)

**SPECIAL NOTE**

- o Add caulking around fixture base at the wall to prevent water from entering fixture.

**INSTALLATION**

- o 4" J-Box
- o 2.50" Deep Octagonal J-Box
- o ETL WET Listed (Installer must provide a bead of caulk between fixture housing and mounting surface)
- o Wall mount
- o Conforms to UL STD 1598
- o Certified CAN/CSA STD C22.2 No. 250.0

**Sample Catalog Number**



Series #	Finish	=	Catalog Number
3-721	24	=	3-721-24

**oxygen**

OXYGEN LIGHTING  
 201 RAILHEAD RD, FORT WORTH, TX 76106  
 TEL. (877) 607-0202 FAX (877) 607-0203  
 WWW.OXYGENLIGHTING.COM

PROJECT: \_\_\_\_\_  
 DATE: \_\_\_\_\_

