



OXYGEN LIGHTING ©

MAIA outdoor
120v 3-741-16
277v 37-741-16

LAMPING	DRIVER (Dimmable)	METAL FINISHES	DIMENSIONS	INSTALLATION
<ul style="list-style-type: none"> o (1x) 12.2w LED Array o 3000K, 350mA o Initial Lumens: 1752 lm o Delivered Lumens: 352 lm o CRI > 80 o Color Consistency: 3 Step MacAdam Ellipse 	<ul style="list-style-type: none"> o (1x) 0-10v & Reverse Phase Dimming, Constant Current, 12w, 350mA 	<ul style="list-style-type: none"> o (All finishes polyester powder coat) o 16 - Gray o 22 - Oiled Bronze 	<ul style="list-style-type: none"> o 12.25" (w) x 2.69" (h) x 3.88" (ext.) o With optional back plate 13.00" (w) x 5.00" (h) x 4.00" (ext.) 	<ul style="list-style-type: none"> o 2" x 3" J-Box o 2.50" Deep 4" Octagonal ETL WET Listed (installer must provide a bead of caulk between fixture housing and mounting surface) o Wall or ceiling mount o Conforms to UL STD 1598 o Certified CAN/CSA STD C22.2 No. 250.0
INPUT VOLTAGE <ul style="list-style-type: none"> o 120v OR 277v 50/60Hz 		DIFFUSER <ul style="list-style-type: none"> o Matte White Acrylic 		
SPECIAL NOTE <ul style="list-style-type: none"> o Add caulking around fixture base at the wall to prevent water from entering fixture. 				

Sample Catalog Number



Series # **3-741** - Finish **22** = Catalog number **3-741-22**

PROJECT: _____

DATE: _____

Oxygen

OXYGEN LIGHTING
201 RAILHEAD RD. FORT WORTH, TX 76106
TEL. (877) 607-0202 FAX (877) 607-0203
WWW.OXYGENLIGHTING.COM

