



OXYGEN LIGHTING ©

MAA outdoor
120v 3-742-16
277v 37-742-16

- | | | | | |
|--|--|---|--|---|
| <p>LAMPING</p> <ul style="list-style-type: none"> <input type="radio"/> (2x) 12.2w LED Arrays <input type="radio"/> 3000K, 350mA (ea.) <input type="radio"/> Initial Lumens: 3504 lm <input type="radio"/> Delivered Lumens: 899 lm <input type="radio"/> CRI>80 <input type="radio"/> Color Consistency: 3 Step MacAdam Ellipse | <p>DRIVER (Dimmable)</p> <ul style="list-style-type: none"> <input type="radio"/> (2x) 0-10v & Reverse Phase Dimming, Constant Current, 12w, 350mA | <p>METAL FINISHES</p> <p>(All finishes polyester powder coat)</p> <ul style="list-style-type: none"> <input type="radio"/> 16 - Gray <input type="radio"/> 22 - Oiled Bronze | <p>DIMENSIONS</p> <ul style="list-style-type: none"> <input type="radio"/> 23.25" (w) x 2.75" (h) x 3.88" (ext.) <input type="radio"/> With optional back plate 24.00" (w) x 5.00" (h) x 4.00" (ext.) | <p>INSTALLATION</p> <ul style="list-style-type: none"> <input type="radio"/> 2" x 3" J-Box <input type="radio"/> 2.50" Deep 4" Octagonal ETL WET Listed (installer must provide a bead of caulk between fixture housing and mounting surface) <input type="radio"/> Wall or ceiling mount <input type="radio"/> Conforms to UL STD 1598 <input type="radio"/> Certified CAN/CSA STD C22.2 No. 250.0 |
| <p>INPUT VOLTAGE</p> <ul style="list-style-type: none"> <input type="radio"/> 120v OR 277v 50/60HZ | <p>DIFFUSER</p> <ul style="list-style-type: none"> <input type="radio"/> Matte White Acrylic | <p>SPECIAL NOTE</p> <ul style="list-style-type: none"> <input type="radio"/> Add caulking around fixture base at the wall to prevent water from entering fixture. | | |

Sample Catalog Number

Series # 3-742 - Finish 22 = Catalog number 3-742-22

PROJECT: _____

DATE: _____



OXYGEN LIGHTING
 201 RAILHEAD RD, FORT WORTH, TX 76106
 TEL. (877) 607-0202 FAX (877) 607-0203
 WWW.OXYGENLIGHTING.COM



