



OXYGEN LIGHTING ©

MAGNUM vanity
 120V **3-588-40**
 277V **37-588-40**

LAMPING

- (2x) 12.2w LED array
- 3000K, 350mA (ea.)
- Initial Lumens: 3504 lm
- Delivered Lumens: 1800 lm
- CRI >80
- Color Consistency: 3 Step MacAdam Ellipse

DRIVER (Dimmable)

- (2x) 0-10v & Reverse Phase Dimming Constant Current, 12w, 350mA

INPUT VOLTAGE

- 120V OR 277V 50/60Hz

METAL FINISHES

- 14** - Polished Chrome
- 24** - Satin Nickel
- 25** - Satin Copper
- 40** - Aged Brass

DIMENSIONS

- 30.75"(w) x 4.75" (h) x 4.00" (ext.)

INSTALLATION

- 2" x 3" J-Box or 4" Octagonal J-Box
- ETL Dry/Damp Listed
- ADA
- Conforms to UL STD 1598
- Certified CAN/CSA STD C22.2 No. 250.0



DIFFUSER

- Matte White Acrylic

Sample Catalog Number

Series #	Finish	Catalog Number
3-588	24	3-588-24

oxygen

OXYGEN LIGHTING
 201 RAILHEAD RD, FORT WORTH, TX 76106
 TEL. (877) 607-0202 FAX (877) 607-0203
 WWW.OXYGENLIGHTING.COM

PROJECT: _____

DATE: _____

